

NINJA ZX-10R SE ABS



BLACK

Please note the image shown above is for illustration purposes only.

Specifications	
ENGINE	
Type	Liquid-cooled, 4-stroke In-Line Four
Displacement	998 cm ³
Bore and Stroke	76.0 x 55.0 mm
Compression Ratio	13.0:1
Valve System	DOHC, 16 valves
Performance:	
a) Maximum power	147.1 kW {200 PS} / 13,000 min ⁻¹
b) Maximum Power With Ram Air	154.4 kW {210 PS} / 13,000 min ⁻¹
c) Maximum torque	113.5 N·m {11.6 kgf·m} / 11,500 min ⁻¹
Fuel System	Fuel injection: ø47 mm x 4 with dual injection
Ignition	Digital
Starting	Electric
Lubrication	Forced lubrication, wet sump with oil cooler
DRIVE TRAIN	
Transmission	6-speed, return
Primary Reduction Ratio	1.681 (79/47)
Gear ratios:	
1st	2.600 (39/15)
2nd	2.214 (31/14)
3rd	1.944 (35/18)
4th	1.722 (31/18)
5th	1.550 (31/20)
6th	1.391 (32/23)
Final reduction ratio	2.294 (39/17)
Clutch	Wet multi-disc, manual
FRAME	
Type	Twin spar, cast aluminium
Caster (rake)	25.0°
Tyre:	
a) Front	120/70ZR17M/C (58W)
b) Rear	190/55ZR17M/C (75W)
SUSPENSION	
Front: Type	ø43 mm inverted Balance Free Front Fork with external compression chamber, KECS-controlled compression and rebound damping, manual spring preload adjustability, and top-out springs
Rear: Type	Horizontal Back-link, BFRC lite gascharged shock with piggyback reservoir, KECS-controlled compression and rebound damping, manual spring preload adjustability, and top-out spring
BRAKES	
Front: Type Caliper:	Dual semi-floating ø330 mm Brembo discs Dual radial-mount, Brembo M50 monobloc, opposed 4-piston
Rear: Type Caliper:	Single ø220 mm disc Single-bore pin-slide, aluminium piston
DIMENSIONS	
Overall length	2,090 mm
Overall width	740 mm
Overall height	1,145 mm
Wheelbase	1,440 mm
Ground clearance	145 mm
Seat height	835 mm
Curb mass	208 kg
Fuel capacity	17 litres

Kawasaki Motors (Malaysia) Sdn. Bhd. reserves the right to alter specifications without prior notice.