

Z250 ABS


GREEN

Please note the image shown above is for illustration purposes only.

Specifications			
ENGINE		FRAME	
Type	Liquid-cooled, 4-stroke Parallel Twin	Type	Trellis, high-tensile steel
Displacement	249 cm ³	Caster (rake)	24.5°
Bore and Stroke	62.0 x 41.2 mm	Tyre:	
Compression Ratio	11.6:1	a) Front	110/70-17 M/C 54H
Valve System	DOHC, 8 Valves	b) Rear	140/70-17 M/C 66H
a) Maximum power	27.5 kW {37 PS} / 12,500 min-1	Wheel travel: front	120 mm
b) Maximum torque	23.0 N.m (2.3 kgf.m) / 10,000 min-1	rear	130 mm
Fuel System	Fuel injection: ø32 mm x 2	Steering angle (left/right)	35° / 35°
Ignition	Digital	SUSPENSION	
Starting	Electric	Front: Type	ø41 mm telescopic fork
Lubrication	Forced lubrication, wet sump	Rear: Type	Bottom-Link Uni-Trak with gas-charged shock with adjustable preload
DRIVE TRAIN		BRAKES	
Transmission	6-speed, return	Front: Type	Single semi-floating ø310 mm petal disc
Final Drive:	Chain	Caliper	Single balanced actuation dual-piston
Primary Reduction Ratio	3.069 (89/29)	Rear: Type	Single ø220 mm petal disc
Gear ratios:		Caliper	Dual-piston
1st	2.769 (36/13)	DIMENSIONS	
2nd	1.895 (36/19)	Overall length	1,990 mm
3rd	1.500 (33/22)	Overall width	800 mm
4th	1.240 (31/25)	Overall height	1,060 mm
5th	1.074 (29/27)	Wheelbase	1,370 mm
6th	0.960 (24/25)	Ground clearance	145 mm
Final reduction ratio	2.857 (40/14)	Seat height	795 mm
Clutch	Wet multi-disc, manual	Curb mass	165 kg
		Fuel capacity	14 litres

Kawasaki Motors (Malaysia) Sdn. Bhd. reserves the right to alter specifications without prior notice.